



Fenner Precision Polymers
Global Corporate Headquarters
187 W. Airport Road, Lititz PA 17543
+1-717-665-2421
www.fenner.com

North America & Latin America
+1-800-243-3374 or +1-717-665-2421
EMEA & APAC
+44 1522 551010 or +44 1522 781800
Italy - MAV S.p.A. a Socio Unico
+39 0461 845151

POWERTWIST DRIVE Link Belting



1

Part Number	Cross Section	Nominal Width	Minimum Pulley Ø	Ride Height Above Rim Min	Ride Height Above Rim Max
0418010SL	3L	3/8 in 10 mm	2.00 in 51 mm	0.12 in 0.17 mm	3.0 in 4.2 mm
0418030SL	A/4L/13	1/2 in 13 mm	3.00 in 80 mm	0.08 in 0.16 mm	2.1 in 4.0 mm
0418050SL	B/5L/17	5/8 in 17 mm	5.00 in 125 mm	0.14 in 0.22 mm	3.4 in 5.6 mm
04100202	3L	3/8 in 10 mm	2.00 in 51 mm	0.12 in 0.17 mm	3.0 in 4.2 mm
04090502M	Z/10	3/8 in 10 mm	1.78 in 45 mm	0.14 in 0.20 mm	3.6 in 5.2 mm
04090302M	A/4L/13	1/2 in 13 mm	3.00 in 80 mm	0.08 in 0.16 mm	2.1 in 4.0 mm
0405010	3L	3/8 in 10 mm	2.00 in 51 mm	0.12 in 0.17 mm	3.0 in 4.2 mm

Part Number	Cross Section	Nominal Width	Minimum Pulley Ø	Ride Height Above Rim Min	Ride Height Above Rim Max
0405030	A/4L/13	1/2 in 13 mm	3.00 in 80 mm	0.08 in 0.16 mm	2.1 in 4.0 mm
0405050	B/5L/17	5/8 in 17 mm	5.00 in 125 mm	0.14 in 0.22 mm	3.4 in 5.6 mm
0405070	C/22	7/8 in 22 mm	9.00 in 229 mm	0.07 in 0.22 mm	1.8 in 5.6 mm
0408010	3L	3/8 in 10 mm	2.00 in 51 mm	0.12 in 0.17 mm	3.0 in 4.2 mm
0408030	A/4L/13	1/2 in 13 mm	3.00 in 80 mm	0.08 in 0.16 mm	2.1 in 4.0 mm
0408050	B/5L/17	5/8 in 17 mm	5.00 in 125 mm	0.14 in 0.22 mm	3.4 in 5.6 mm
0408070	C/22	7/8 in 22 mm	9.00 in 229 mm	0.07 in 0.22 mm	1.8 in 5.6 mm
0410020	Z/10	3/8 in 10 mm	1.78 in 45 mm	0.14 in 0.20 mm	3.6 in 5.2 mm
0410030	A/4L/13	1/2 in 13 mm	3.00 in 80 mm	0.08 in 0.16 mm	2.1 in 4.0 mm
0410050	B/5L/17	5/8 in 17 mm	5.00 in 125 mm	0.14 in 0.22 mm	3.4 in 5.6 mm
0410070	C/22	7/8 in 22 mm	9.00 in 229 mm	0.07 in 0.22 mm	1.8 in 5.6 mm
0418023	Z/10	3/8 in 10 mm	1.78 in 45 mm	0.14 in 0.20 mm	3.6 in 5.2 mm
0418033	A/4L/13	1/2 in 13 mm	3.00 in 80 mm	0.08 in 0.16 mm	2.1 in 4.0 mm
0418053	B/5L/17	5/8 in 17 mm	5.00 in 125 mm	0.14 in 0.22 mm	3.4 in 5.6 mm

Part Number	Cross Section	Nominal Width	Minimum Pulley Ø	Ride Height Above Rim Min	Ride Height Above Rim Max
-------------	------------------	------------------	---------------------	------------------------------	------------------------------

0418073	C/22	7/8 in 22 mm	9.00 in 229 mm	0.07 in 0.22 mm	1.8 in 5.6 mm
---------	------	-----------------	-------------------	--------------------	------------------