



TOUCH SCREEN OPERATOR PANEL WITH PLC INTEGRATED

TSP 240



MAIN FEATURES

- Graphic LCD display with high contrast (320x240 pixels). Blue background with white written.
- Touch screen with tactile sensation and buzzer
- Until 64 Kbyte FLASH memory for PLC program, 1 Mbyte Flash memory for operator panel program, 64 kbyte EEPROM memory, 200 byte not volatile RAM memory
- N° 20 PNP digital Inputs with 4 fast inputs and 2 for line driver Encoder
- N° 16 static outputs (24VDC, 0,5 A)
- N° 8 analogic inputs, 4 configurable for PT100, J or K Thermocouples, current or voltage and 4 for current or voltage
- N° 4 +/- 10 V - 12 bit and N°2 PWM - 14 bit analogic outputs
- Optional Ethernet port with Web Server function
- N° 2 serial interface configurable
- USB Master and Slave
- Standard and personalized communication protocols for PLC or other connections
- C language or AWL (instruction list) or graphic ladder programming (graphic ladder development)
- Special functions for PID regulators, step motor and electronic cams management
- Extractable terminal boards
- AC or DC power supply with large range (15/22 AC, 15/26 DC)
- Size: 169x126,50 mm frontal, 90 mm depth.

Rivenditore o agente

