

# **BO42(70W)**



## **Design**

BO4227 Series Motors are Brushless DC Outrunner motors with 43mm diameter and 27mm height. These Motors are available with sensor and without sensor. Robust Ball bearings ensure excellent service life with ≥5000Hrs. Drivers are also available as an Add-On unit on special request. These motors are available in different speeds and different voltages on special request. In order to reduce motor height, we can use FFC cable also on the special request.

#### **Standard Data**

Motor Type		Outrunner Brushless dc motor	
Configuration		12N-16P	
Ambient Temperature Operation		-40°C to +100°C	
Storage & Transport Temperature		-60°C to +120°C	
Weight	g	140	
Electrical Enclosure		40 (As per IEC 60529)	
Life expectancy		≥5000 hours @ Rated Torque	

### **Available Customizations**


Sensorless
Inbuilt driver
Customized motor speed
Dust cover (Upto IP 65 **)
22 AWG x 200mm ends tinned & stripped
Customized shaft
Hollow shaft for robotics and gimbal applications

## **Technical Data**

MECHTEX	Physical data	No load data			Data at Rated Torque				Stall	
MODEL No.	Dia x height	Voltage	Speed	Current	Speed	Current	Torque	Power	Torque	Current
	mm	V DC	RPM	mA	RPM	Α	cNm	W(out)	cNm	Α
BO4227-24b	43 X 27	24	5600	340	4100	3	13	53.3	150	44
BO4227-24b	43 X 27	24	7200	500	5920	3	9	53.3	142	48

<sup>\*</sup>Other speeds & voltages on special request

## **Dimensional Drawing**



16 www.mechtex.com

<sup>\*\*</sup> On special request