



Power [kW] <b>2.2</b>	Base speed [rpm] <b>18000</b>	Base voltage [V] <b>220/380</b>	Base frequency [Hz] <b>300</b>	<b>TEKNOMOTOR</b>
Min speed [rpm] <b>9000</b>	Max speed [rpm] <b>18000</b>	Part number <b>51600241</b>	Internal code <b>51600241</b>	
grado di equilibratura: 2.5 norma ISO 1940	equilibratura / balancing -	tool full key	tool half key	peso / weight
Tolleranze non quotate: ±0.5mm Smussi non quotati: ±0.5mm		$\nabla = 0.8 \nabla$	$\nabla = 3.2 \nabla$	$\nabla = 12.5 \nabla$
revisione n° <b>0</b>	motivo di revisione <b>Prima emissione</b>			titolo/title <b>Bialbero 5160-A-SB-P-ER25</b>
dis. da / drawn <b>Ing. Bottarel</b>	appr. da / approved <b>Ing. Perli</b>	data / date <b>21/04/2010</b>	sostituisce il sostituito dal	Cliente/Customer <b>Catalogo</b>
percorso / path		codice / drawing code <b>5Com51600241</b>		disegno n° / drawing n° <b>2190</b>
		foglio / sheet <b>1 / 2</b>	scala <b>1:2</b>	<b>A4</b>